

Covinax 081-00

PRODUCT DESCRIPTION

Covinax 081-00 is a pressure sensitive, vinyl acrylic copolymer stabilized with a cellulosic colloid. The performance of this pressure sensitive emulsion is characterized by moderate peel adhesion, high shear resistance, and good quick tack. COVINAX 081-00 is thixotropic and has excellent mechanical stability. COVINAX 081-00 exhibits excellent adhesion to Mylar and cellophane.

PHYSICAL PROPERTIES

Polymer Type:Vinyl AcrylicFreeze/Thaw Stability:UnstableProtective System:Anionic/CellulosicWeight per Gallon (lbs):8.4Viscosity (cps):100 - 800 (LVF, Spindle #3/60RPM/77°F)Borax Compatible:Yes

Percent Solids:52% - 55%Surface Tension:33 dynes/cm.pH:4.2 - 5.2Shelf Life:6 months

ADDITIONAL INFORMATION

A 1 mil $(28g/M^2)$ dry film of Covinax 081-00 cast directly onto 1 mil thickness polyester film will exhibit the following average performance properties when tested on #304 stainless steel, which has a #3 surface finish.

Test 180° Peel ¹ 178° Shear ² Loop Tack³ Performance Values

2.0 pounds 700 minutes 1.8 pounds

The data provided in this Technical Data Sheet represents typical physical and/or performance values for the product under a given set of testing conditions. The ranges or values are not specifications. Specifications will be set based on statistical analysis of measurements made by the quality control laboratory on production material and will accurately reflect production capabilities. This data should be used as a guide for product selection only.

Important Notice to Purchaser: Our recommendations, if any, for use of this product are based on tests believed to be reliable. The greatest care is exercised in the selection of our materials and in our manufacturing operations. However, we make no recommendation to use this product in any manner which conflicts with existing laws and/or patents and WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS PRODUCT OR ITS USE, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE, THE MANUFACTURER IS NOT LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES OF ANY KIND. Revised 07/14/08.

©Copyright 2008. All rights reserved. Franklin International.



¹ Franklin International 03QC5002, 30 minute dwell

² Franklin International 03QC5003, 0.25 square inch, 500 gram load

³ Franklin International 03QC5004, 1 square inch contact, 1 second dwell