

Franklin's recommended products

Advantage 160

Highly water-resistant, exceeds ASTM D-5572 wet-use performance and ideal for finger jointing, edge gluing, radio frequency applications and hot pressing.

Advantage 405 & 415

Highly water-resistant two-part adhesives that surpass both the ASTM D-5572 wet-use finger joint and ASTM D-5751 wet-use laminate standard.

Advantage 425

Designed for finger jointing applications requiring excellent water-resistance and high performance. It surpasses the requirements for ASTM D-5572 wet use.

Multibond EZ-2

Designed for cold press applications including finger jointing, but can also be used for radio frequency, assembly and hot press gluing. It has a low minimum use temperature.

Multibond X-016

Highly water-resistant adhesive ideal for finger jointing, cold press, radio-frequency and hot-press applications.

ReacTITE 8143

A one-component, low foam, moisture-curing adhesive designed for finger jointing applications. It is a 100% solids adhesive that eliminates the VOCs and waste associated with many traditional adhesives.

Woodbond F

Cost-effective, fast-setting PVA well-suited for finger jointing, doweling and general assembly work. Its low viscosity makes it easy to spread by mechanical adhesive applicators.

Woodbond X-338

Used in finger jointing of interior stock and capable of passing the ASTM-5572 dry use three cycle water soak while maintaining a high level of heat resistance.

Woodbond 1910

Ideal for finger jointing of interior stock and has excellent handling properties, high heat resistance and easy extrusion capabilities.

Woodbond 1920

One-component ASTM D-5572 interior use adhesive with shear thinning rheology which makes it ideal for extrusion on finger joints. It can be mixed with Catalyst A to provide ASTM D-5572 wet use performance.

Technical Leadership

With over 70 years of combined hands-on experience, our technical support team is one of the most recognized and respected in the industry. We welcome your calls and encourage you to contact us if you have any questions or concerns regarding any of our finger jointing adhesives.



For additional support, try our pressure point calculators available 24/7 online at www.FranklinAdhesivesandPolymers.com. With our collection of online calculators, you can determine the appropriate settings and costs when using our adhesives for finger jointing.

1.800.877.4583



gluing guide Adhesives for Finger Jointing



Franklin 
Adhesives & Polymers

Corporate Office
Franklin International
2020 Bruck Street Columbus, Ohio USA 43207
T 1.800.877.4583 F 614.445.1555
E marketing@franklininternational.com

Franklin 
Adhesives & Polymers

